



- dimensiunile mari, atat ale platformei de lucru (500 x 500 mm) cat si ale treptelor de urcare (500 x 80 mm) asigura o utilizare comoda a produsului
- scara SPMI este mobila fiind deplasabila usor datorita celor doua roti fixe cu frana (diametrul de 125 mm) de la baza
- executie conform normelor **SR EN 131-7**
- incarcare maxima admisibila: **150kg**
- material lonjeroane si suporti: aluminiu **AlMgSi**
- material trepte: **aluminiu nervurat** (pentru evitarea alunecarii)
- material platforma: **aluminiu striat** (pentru aderenta sporita in lucru)
- Diferenta intre SPMF si SPMI este ca la SPMF treptele cu adancimea de **80 mm** sunt asigurate suplimentar cu trepte de **28 x 28 mm** incastrate in lonjeroanele scarii iar la SPMI se folosesc numai trepte de **28 x 28 mm**
- OBS: In TABEL la rubrica "Nr. trepte" este adaugata si platforma



Cod	Nr. trepte	Inaltime platforma [m]	Inaltime totala [m]	Masa [kg]	Inaltime max. de lucru [m]
SPMI 3	3	0,8	1,8	14,7	2.8
SPMI 4	4	1,0	2,0	16,7	3.0
SPMI 5	5	1.3	2,1	18,7	3.3
SPMI 6	6	1,6	2,6	20,7	3.6
SPMI 7	7	1,8	2,8	22,1	3.8
SPMI 8	8	2,1	3,1	23,7	4.1
SPMI 9	9	2,4	3,4	25,5	4.4
SPMI 10	10	2,6	3,6	27,3	4.6
SPMI 11	11	2,9	3,9	28,1	4.9
SPMI 12	12	3,1	4,1	29,1	5.1
SPMI 13	13	3,4	4,4	30,9	5.4
SPMI 14	14	3,7	4,7	32,7	5.7
SPMI 15	15	3,9	4,9	33,1	5.9

Caracteristici produs:



Caracteristici generale

- pliabila
- latime tronson scara: **550 mm**
- dimensiuni lonjeroane: **61,4 x 23 mm**
- grosime pereti trepte: **1,3 mm** - grosime pereti lonjeroane : **1,3 mm** pana la SPMI 8 **1,7 mm** de la SPMI 10 la

SPMI 14

- platforma de sus din aluminiu striat
- aria platformei: **500 x 500 mm**
- protectie la deschidere rigida
- diametrul roti: **125 mm**