

Scara dubla cu platforma si roti cu arc, tip PDRA



- executie conform normelor **SR EN 131-7**
- incarcare maxima admisibila: **150kg**
- material lonjeroane si suporti: **aluminiiu AIMgSi**
- material trepte: **aluminiiu nervurat** (pentru evitarea alunecarii)
- material platforma: **aluminiiu striat** (pentru aderenta sporita in lucru)
- pentru cresterea sigurantei in functionare, treptele cu adancimea de **80 mm** sunt asigurate suplimentar cu trepte de **28 x 28 mm** incastrate in lonjeroanele scarii
- Deplasarea este realizata cu **4 roti cu frana si arc** montate pe traversele de rigidizare. La pozitia de lucru, operatorul blocheaza rotile iar apoi se urca pe platforma. Datorita greutatii operatorului, arcurile rotilor se comprima iar dopurile de plastic antiderapant de la baza intra in contact cu podeaua blocand platforma pe pozitia respectiva



Tip	Nr.trepte	Inaltime platforma [m]	Inaltime totala [m]	Lungime totala [m]	Masa [kg]	Inaltime max. de lucru [m]
PDRA3	2x3	0,7	1,8	1,2	12,0	2.7
PDRA4	2x4	1,0	2,1	1,4	13,5	3.0
PDRA5	2x5	1,2	2,3	1,6	15,0	3.2
PDRA6	2x6	1,5	2,6	1,7	16,5	3.5
PDRA7	2x7	1,7	2,8	1,9	18,0	3.7
PDRA8	2x8	2,0	3,1	2,1	20,0	4.0



Caracteristici produs:

COMPONENTA PRODUS

- 2 buc.balustrade platforma
- 4 buc. balustrade scari
- o platforma
- 2 buc. scari
- 2 buc. rigidizari



Caracteristici generale

- inaltime balustrade platforma: **1100 mm**
- latime tronsoane scara: **550 mm**
- grosime trepte: **30 mm**
- latime trepte: **80 mm**
- balustrade din teava rotunda de **25x2 mm**
- distanta intre trepte: **260 mm**
- platforma de sus din **aluminiiu striat**
- aria platformei: **550 x 700 mm**- **capace** de plastic la terminatiile balustradelor
- **dopuri** de plastic **antiderapante** la baze
- **4 roti cu frana si arc** de diametru **100 mm**

