

Platforma RARIS la 60 ⁰, mobila, din otel, in consola, blocare la picior, cod PMCE.



- executie conf. normei **EN ISO 14122 si SR EN 131-7**
- panta de urcare: **60 grade**
- lonjeroane, balustrade, legaturi : **otel vopsit in pulbere**
- trepte : **tabla striata otel de 3 mm**
- inaltimea de lucru maxima este **inaltimea podinii plus 1,8 metri**
- greutatea maxima suportata :

a) pe podina: **300 kg**

b) pe o treapta: **200 kg**

- DEPLASAREA este realizata cu **2 roti fixe de 200 mm** si un **dispozitiv de deplasare cu 2 roti de 125 mm** ce are si rol de BLOCARE PLATFORMA prin actionare la picior (vezi si filmul atasat)



Cod	Nr trepte produs	Inaltime podina [m]	Inaltime totala [m]	Masa [kg]	Inaltime maxima de lucru [m]
PMCE6	6	1.5	2.5	97	3.3
PMCE8	8	2.0	3.0	128	3.8
PMCE10	10	2.5	3.5	157	4.3
PMCE12	12	3.0	4.0	189	4.8
PMCE14	14	3.5	4.5	221	5.3



Caracteristici produs:



Caracteristici:- dimensiuni podina:: **700x500 mm**- latime trepte: **800 mm** - distanta intre doua trepte consecutive
a) pe verticala: **250 mm** b) pe orizontala: **144 mm**-
inaltime balustrada podina : **1000 mm**- inaltime balustrada perpendicular pe scara: **700 mm**
- doua tavi pentru scule in partea superioara

