

Scara aluminiu RARIS, fixa, la 60 grade, profile sistem, tip ETP60



- executie conform normei **EN ISO 14122 si EN131**
- panta de urcare: **60 grade**
- material: profile sistem aluminiu **AlMgSi**
- elementele de asamblare: otel zincat
- greutatea maxima suportata :

a) pe produs: **300 kg**

b) pe o treapta: **200 kg**

- inaltimea maxima de lucru: **H + 2 metri** (H este inaltimea ultimei trepte de sus)
- **H = 1000 -:- 4500 mm;**
- **L = 725 -:- 2755 mm;**
- **Nr. trepte = 4 -:- 18.**

OBS1: In TABEL, la pozitia "Nr trepte", se considera si podina ca treapta
OBS2: Produsul trebuie incastrat la baza si in peretii de sprijin (in partea superioara) printr-un SISTEM DE FIXARE pus la dispozitie de producator si executat dupa consultari cu beneficiarul scarii

Cod produs	Inaltime scara[mm]	Amprenta orizontala scara[mm]	Nr. trepte	Masa [kg]	Inaltime max. de lucru [m]
ETP6064	1000	580	4	14.4	3.00
ETP6065	1250	725	5	17.5	3.25
ETP6066	1500	870	6	20.7	3.50
ETP6067	1750	1015	7	24.0	3.75
ETP6068	2000	1160	8	27.2	4.00
ETP6069	2250	1350	9	30.4	4.25
ETP60610	2500	1450	10	33.5	4.50
ETP60611	2750	1595	11	36.7	4.75
ETP60612	3000	1740	12	39.9	5.00
ETP60613	3250	1885	13	43.1	5.25
ETP60614	3500	2030	14	46.4	5.50
ETP60615	3750	2175	15	49.5	5.75
ETP60616	4000	2320	16	52.7	6.00
ETP60617	4250	2465	17	55.9	6.25
ETP60618	4500	2610	18	59.1	6.50

Cod produs	Inaltime scara [mm]	Amprenta orizontala scara [mm]	Nr. trepte	Masa [kg]	Inaltime max. de lucru [m]
ETP6084	1000	580	4	16	3.00
ETP6085	1250	725	5	20.7	3.25
ETP6086	1500	870	6	24.0	3.50
ETP6087	1750	1015	7	27.2	3.75
ETP6088	2000	1160	8	31.1	4.00

Scara aluminiu RARIS, fixa, la 60 grade, profile sistem, tip ETP60

ETP6089	2250	1305	9	35.2	4.25
ETP60810	2500	1450	10	38.4	4.50
ETP60811	2750	1595	11	41.5	4.75
ETP60812	3000	1740	12	46.4	5.00
ETP60813	3250	1885	13	49.5	5.25
ETP60814	3500	2030	14	52.7	5.50
ETP60815	3750	2175	15	57.5	5.75
ETP60816	4000	2320	16	60.7	6.00
ETP60817	4250	2465	17	63.9	6.25
ETP60818	4500	2610	18	68.7	6.50
Cod produs	Inaltime scara [mm]	Amprenta orizontala scara [mm]	Nr. trepte	Masa [kg]	Inaltime max. de lucru [m]
ETP60104	1000	725	4	17.3	3.00
ETP60105	1250	870	5	22.4	3.25
ETP60106	1500	1015	6	37.2	3.50
ETP60107	1750	1160	7	30.4	3.75
ETP60108	2000	1305	8	35.2	4.00
ETP60109	2250	1450	9	39.9	4.25
ETP601010	2500	1595	10	43.1	4.50
ETP601011	2750	1740	11	48.0	4.75
ETP601012	3000	1885	12	52.7	5.00
ETP601013	3250	2030	13	55.9	5.25
ETP601014	3500	2175	14	60.7	5.50
ETP601015	3750	2320	15	65.4	5.75
ETP601016	4000	2465	16	68.7	6.00
ETP601017	4250	2610	17	73.4	6.25
ETP601018	4500	2755	18	78.3	6.50

Caracteristici produs:



Caracteristici: - latime trepte: 600 / 800 / 1000 mm- grosime trepte: 40 mm- adancime trepte: 175 mm- distanta intre doua trepte consecutive a) pe verticala: 250 mm b) pe orizontala: 145 mm- inaltime balustrada: 500 mm (perpendicular pe scara)- suprafata treptelor: aluminiu striat