

Platforma fixa RARIS, profile aluminiu sistem, la 60 grade, Gmax = 400 kg - tip PPF60



- executie conform normei **EN ISO 14122 si EN131**
- panta de urcare: **60 grade**
- material: profile sistem aluminiu **AlMgSi**
- elementele de asamblare: otel zincat
- greutatea maxima suportata :

a) pe produs: **400 kg**

b) pe o treapta: **200 kg**

- adancimea podinii: **700 mm** (latimea egala cu cea a treptelor)
- inaltimea maxima de lucru: **H + 2 metri** (H este inaltimea podinii considerata si ultima treapta de sus)
- **H = 1000 -:- 4500 mm;**
- **L = 725 -:- 2755 mm;**
- Nr. trepte = **4 -:- 18.**

OBS1: In TABEL, la pozitia "Nr trepte", se considera si podina ca treapta

OBS2: Produsul trebuie incastrat in pardosea printr-un sistem de corniere zincate puse la dispozitie de producator.

Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma[m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60A64	4	1,0	2,1	1,2	37.2	3.0
PPF60A65	5	1,2	2,3	1,3	41.4	3.2
PPF60A66	6	1,5	2,6	1,5	45.4	3.5
PPF60A67	7	1,7	2,8	1,6	49.6	3.7
PPF60A68	8	2,0	3,1	1,8	53.8	4.0
PPF60A69	9	2,2	3,3	1,9	59.3	4.2
PPF60A610	10	2,5	3,6	2,1	63.5	4.5
PPF60A611	11	2,7	3,8	2,2	67.7	4.7
PPF60A612	12	3,0	4,1	2,3	71.8	5.0
PPF60A613	13	3,2	4,3	2,5	76.0	5.2
PPF60A614	14	3,5	4,6	2,6	81.7	5.5
PPF60A615	15	3,7	4,8	2,8	85.2	5.7
PPF60A616	16	4,0	5,1	2,9	89.9	6.0
PPF60A617	17	4,2	5,3	3,1	94.0	6.2
PPS60A618	18	4,5	5,6	3,2	98.1	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60T64	4	1,0	2,1	1,2	38.7	3.0
PPF60T65	5	1,2	2,3	1,3	43.7	3.2
PPF60T66	6	1,5	2,6	1,5	48.5	3.5
PPF60T67	7	1,7	2,8	1,6	53.5	3.7
PPF60T68	8	2,0	3,1	1,8	58.4	4.0
PPF60T69	9	2,2	3,3	1,9	64.8	4.2

Platforma fixa RARIS, profile aluminiu sistem, la 60 grade, Gmax = 400 kg - tip PPF60

PPF60T610	10	2,5	3,6	2,1	69.6	4.5
PPF60T611	11	2,7	3,8	2,2	74.6	4.7
PPF60T612	12	3,0	4,1	2,3	77.7	5.0
PPF60T613	13	3,2	4,3	2,5	84.4	5.2
PPF60T614	14	3,5	4,6	2,6	90.7	5.5
PPF60T615	15	3,7	4,8	2,8	95.7	5.7
PPF60T616	16	4,0	5,1	2,9	100.6	6.0
PPF60T617	17	4,2	5,3	3,1	105.3	6.2
PPF60T618	18	4,5	5,6	3,2	110.3	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60G64	4	1,0	2,1	1,2	36.1	3.0
PPF60G65	5	1,2	2,3	1,3	40.2	3.2
PPF60G66	6	1,5	2,6	1,5	44.2	3.5
PPF60G67	7	1,7	2,8	1,6	48.3	3.7
PPF60G68	8	2,0	3,1	1,8	52.1	4.0
PPF60G69	9	2,2	3,3	1,9	57.6	4.2
PPF60G610	10	2,5	3,6	2,1	61.5	4.5
PPF60G611	11	2,7	3,8	2,2	65.6	4.7
PPF60G612	12	3,0	4,1	2,3	69.5	5.0
PPF60G613	13	3,2	4,3	2,5	73.5	5.2
PPF60G614	14	3,5	4,6	2,6	78.9	5.5
PPF60G615	15	3,7	4,8	2,8	83.0	5.7
PPF60G616	16	4,0	5,1	2,9	86.9	6.0
PPF60G617	17	4,2	5,3	3,1	91.0	6.2
PPF60G618	18	4,5	5,6	3,2	94.9	6.5
PPF60A1018	18	4,5	5,6	3,2	125.8	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60T104	4	1.0	2.1	1.2	48.5	3.0
PPF60T105	5	1.2	2.3	1.3	55.0	3.2
PPF60T106	6	1.5	2.6	1.5	61.5	3.5
PPF60T107	7	1.7	2.8	1.6	67.9	3.7
PPF60T108	8	2.0	3.1	1.8	74.3	4.0
PPF60T109	9	2.2	3.3	1.9	82.6	4.2
PPF60T1010	10	2.5	3.5	2.1	89.1	4.5
PPF60T1011	11	2.7	3.7	2.2	95.7	4.7
PPF60T1012	12	3.0	4.1	2.3	101.9	5.0
PPF60T1013	13	3.2	4.3	2.5	108.4	5.2
PPF60T1014	14	3.5	4.6	2.6	116.8	5.5
PPF60T1015	15	3.7	4.8	2.8	123.3	5.7
PPF60T1016	16	4.0	5.1	2.9	129.8	6.0
PPF60T1017	17	4.2	5.3	3.1	136.3	6.2

Platforma fixa RARIS, profile aluminiu sistem, la 60 grade, Gmax = 400 kg - tip PPF60

PPF60T1018	18	4.5	5.6	3.2	142.6	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60G104	4	1.0	2.1	1.2	45.4	3.0
PPF60G105	5	1.2	2.3	1.3	50.4	3.2
PPF60G106	6	1.5	2.6	1.5	55.6	3.5
PPF60G107	7	1.7	2.8	1.6	60.7	3.7
PPF60G108	8	2.0	3.1	1.8	65.8	4.0
PPF60G109	9	2.2	3.3	1.9	72.6	4.2
PPF60G1010	10	2.5	3.6	2.1	77.7	4.5
PPF60G1011	11	2.7	3.8	2.2	82.9	4.7
PPF60G1012	12	3.0	4.1	2.3	87.9	5.0
PPF60G1013	13	3.2	4.3	2.5	93.1	5.2
PPF60G1014	14	3.5	4.6	2.6	100.0	5.5
PPF60G1015	15	3.7	4.8	2.8	105.2	5.7
PPF60G1016	16	4.0	5.1	2.9	110.2	6.0
PPF60G1017	17	4.2	5.3	3.1	115.3	6.2
PPF60G1018	18	4.5	5.6	3.2	120.4	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60A84	4	1,0	2,1	1,2	42.3	3.0
PPF60A85	5	1,2	2,3	1,3	47.0	3.2
PPF60A86	6	1,5	2,6	1,5	51.6	3.5
PPF60A87	7	1,7	2,8	1,6	56.4	3.7
PPF60A88	8	2,0	3,1	1,8	61.1	4.0
PPF60A89	9	2,2	3,3	1,9	67.3	4.2
PPF60A810	10	2,5	3,6	2,1	72.1	4.5
PPF60A811	11	2,7	3,8	2,2	76.7	4.7
PPF60A812	12	3,0	4,1	2,3	81.4	5.0
PPF60A813	13	3,2	4,3	2,5	86.1	5.2
PPF60A814	14	3,5	4,6	2,6	92.2	5.5
PPF60A815	15	3,7	4,8	2,8	96.9	5.7
PPF60A816	16	4,0	5,1	2,9	101.5	6.0
PPF60A817	17	4,2	5,3	3,1	106.3	6.2
PPF60A818	18	4,5	5,6	3,2	111.0	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60T84	4	1,0	2,1	1,2	43.9	3.0
PPF60T85	5	1,2	2,3	1,3	49.5	3.2
PPF60T86	6	1,5	2,6	1,5	55.2	3.5
PPF60T87	7	1,7	2,8	1,6	60.8	3.7
PPF60T88	8	2,0	3,1	1,8	66.4	4.0

Platforma fixa RARIS, profile aluminiu sistem, la 60 grade, Gmax = 400 kg - tip PPF60

PPF60T89	9	2,2	3,3	1,9	75.3	4.2
PPF60T810	10	2,5	3,6	2,1	79.2	4.5
PPF60T811	11	2,7	3,8	2,2	84.6	4.7
PPF60T812	12	3,0	4,1	2,3	90.3	5.0
PPF60T813	13	3,2	4,3	2,5	96.0	5.2
PPF60T814	14	3,5	4,6	2,6	103.1	5.5
PPF60T815	15	3,7	4,8	2,8	109.0	5.7
PPF60T816	16	4,0	5,1	2,9	114.4	6.0
PPF60T817	17	4,2	5,3	3,1	120.0	6.2
PPF60T818	18	4,5	5,6	3,2	125.6	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60G84	4	1,0	2,1	1,2	41.1	3.0
PPF60G85	5	1,2	2,3	1,3	45.4	3.2
PPF60G86	6	1,5	2,6	1,5	49.9	3.5
PPF60G87	7	1,7	2,8	1,6	54.5	3.7
PPF60G88	8	2,0	3,1	1,8	58.8	4.0
PPF60G89	9	2,2	3,3	1,9	65.0	4.2
PPF60G810	10	2,5	3,6	2,1	69.4	4.5
PPF60G811	11	2,7	3,8	2,2	73.8	4.7
PPF60G812	12	3,0	4,1	2,3	78.4	5.0
PPF60G813	13	3,2	4,3	2,5	82.7	5.2
PPF60G814	14	3,5	4,6	2,6	89.0	5.5
PPF60G815	15	3,7	4,8	2,8	93.3	5.7
PPF60G816	16	4,0	5,1	2,9	97.7	6.0
PPF60G817	17	4,2	5,3	3,1	102.2	6.2
PPF60G818	18	4,5	5,6	3,2	106.7	6.5
Cod produs	Nr. trepte	Inaltime podina[m]	Inaltime platforma [m]	Lungime platforma [m]	Masa [kg]	Inaltime max. de lucru [m]
PPF60A104	4	1,0	2,1	1,2	46.9	3.0
PPF60A105	5	1,2	2,3	1,3	52.4	3.2
PPF60A106	6	1,5	2,6	1,5	57.7	3.5
PPF60A107	7	1,7	2,8	1,6	63.1	3.7
PPF60A108	8	2,0	3,1	1,8	68.5	4.0
PPF60A109	9	2,2	3,3	1,9	75.6	4.2
PPF60A1010	10	2,5	3,6	2,1	81.1	4.5
PPF60A1011	11	2,7	3,8	2,2	86.5	4.7
PPF60A1012	12	3,0	4,1	2,3	91.8	5.0
PPF60A1013	13	3,2	4,3	2,5	97.2	5.2
PPF60A1014	14	3,5	4,6	2,6	104.2	5.5
PPF60A1015	15	3,7	4,8	2,8	109.8	5.7
PPF60A1016	16	4,0	5,1	2,9	115.2	6.0
PPF60A1017	17	4,2	5,3	3,1	120.4	6.2

Caracteristici produs:



Caracteristici:- grosime trepte: **40 mm**
 - adancime trepte: **175 mm**- distanta intre doua trepte consecutive a) pe verticala: **250 mm** b) pe orizontala: **145 mm**- inaltime balustrade: **500 mm** (perpendicular pe scara)- material suprafata trepte si podina: **aluminiu striat**

