

Minischela aluminiu tip PROFI: MW1.6



constructiv si din punct de vedere al sigurantei, miniscelele de aluminiu indeplinesc cerintele normei **EN 1004/2005, grupa III**, deci cu o incarcare maxima admisa de **200 kg/m²** elementele componente sunt executate din aliaj de **aluminiu extrudat** (nu tabla sudata)

podurile de lucru sunt placate cu **tego antiderapant** de 10 mm grosime

Componente minischela aluminiu:

- traversa baza MUW1,6: 2 buc.
- diagonala baza MW1,6: 1 buc.
- scara modul W: 2 buc.
- scara capat W: 2 buc.
- rigidizare modul 1,6: 2 buc.
- traversa capat MUW1,6: 2 buc.
- podina cu trapa 1,6: 1 buc.
- podina fara trapa 1,6: 1 buc.
- diagonala modul 1,6: 2 buc.

Minischela poate fi transformata in **minischela mobila** prin adaugarea **Modulului roti pentru miniscele** ce are in componenta 4 roti pivotante cu frana si diametrul de 125 mm



Tip	Masa [kg]	Inaltime max. de lucru [m]
Minischela aluminiu tip: MW1,6	77	4.5
Modul roti pentru miniscele	4.8	-

Caracteristici produs:



Caracteristici minischela aluminiu:

- inaltimea maxima podina: **2,2 m**
- inaltimea maxima schela: **3,2 m**
- inaltimea maxima de lucru: **4,5 m**
- podina din aluminiu: **suprafata 1,6 x 1,4 m**;
- greutatea proprie: **77 kg**

