

Minischela aluminiu tip PROFI: MW2.5



constructiv si din punct de vedere al sigurantei, miniscelele de aluminiu indeplinesc cerintele normei **EN 1004/2005, grupa III**, deci cu o incarcare maxima admisa de **200 kg/m²**

elementele componente sunt executate din aliaj de **aluminiu extrudat** (nu tabla sudata)

podurile de lucru sunt placate cu **tego antiderapant** de 10 mm grosime

Componente minischela aluminiu:

- traversa baza MUW2,5: 2 buc.
- diagonala baza MW2,5: 1 buc.
- scara modul W: 2 buc.
- scara capat W: 2 buc.
- rigidizare modul 2,5: 2 buc.
- traversa capat MUW2,5: 2 buc.
- podina cu trapa 2,5: 1 buc.
- podina fara trapa 2,5: 1 buc.
- diagonala modul 2,5: 2 buc.

minischela de aluminiu poate fi transformata in **minischela mobila** prin adaugarea **Modulului roti pentru miniscele** ce are in componenta 4 roti pivotante cu frana si diametrul de 125 mm



Tip	Masa [kg]	Inaltime max. de lucru [m]
Minischela aluminiu tip: MW2,5	86	4.5
Modul roti pentru miniscele	4.8	-

Caracteristici produs:



Caracteristici minischela aluminiu:

- inaltimea maxima podina: 2,2 m
- inaltimea maxima schela: 3,2 m
- inaltimea maxima de lucru: 4,5 m
- podina din aluminiu: suprafata 2,5 x 1,4 m;
- greutatea proprie: 86 kg

